Assessment Guidelines for TABLE A-II/4

Specification for minimum standard of competency

Proficiency in Rating Forming Part of a Navigational Watch

Skills that must be demonstrated:

USCC-2000-7373-2

1. Use of magnetic and gyro-compasses;

- 2. Respond to standard rudder orders (Hard right [starboard] or left [port]; ease the rudder; midships; shift your rudder; meet her; steady as she goes; steer on the range);
- 3. Change over from automatic to hand steering;
- 4. Certain responsibilities of the lookout (reporting sounds, lights and objects);
- 5. Watch procedures that contribute to a safe watch (relief, maintenance and hand over).

The following knowledge or understanding-based competencies may be assessed through a written multiple-choice examination. The examination should also assess the knowledge or understanding required to perform the skill demonstrations listed above. The candidate must achieve a minimum passing grade of 70% in each area of knowledge or understanding within the competency.

- 1. Shipboard terms and definitions related to lookout (reporting sounds, lights and objects);
- 2. Information requirements that contribute to a safe watch;
- 3. Basic environmental procedures that contribute to a safe watch;
- 4. Knowledge of duties and signals needed to operate emergency equipment and apply emergency procedures;
- 5. Knowledge of pyrotechnic distress signals, EPIRBs and SARTs needed to operate emergency equipment and apply emergency procedures, including false alarms and accidental activation.

Skill demonstrations

As part of a proficiency in Rating Forming Part of a Navigational Watch assessment, candidates must meet the standards of competence set out in STCW Code Table A-II/4. The candidates will demonstrate their competence to (1) steer the ship and comply with helm orders; (2) keep a proper look out; and (3) contribute to a safe watch. Each candidate must perform every required demonstration using actual equipment or an approved full mission simulator. All steering and helm assessments must occur on a vessel of at least 100 gross tons or a full mission ship simulator programmed to realistically simulate the hydrodynamic properties of vessels of at least 200 GRT (500 ITC), equipped with a rudder order indicator, a rudder angle indicator, gyrocompass, magnetic compass, and a steering stand which permits the steering to be switched from hand to gyro. The assessment of the ability to contribute to monitoring and controlling a safe watch must occur aboard a ship at sea.

These assessment guidelines establish the conditions under which the assessment will occur, the performance or behavior the candidate is to accomplish, and the standards against which the performance is measured. The examiner is encouraged to use a checklist in conducting assessments of practical demonstrations of skill. Checklists allow a training institution or designated examiner to ensure that critical tasks are not overlooked when evaluating a candidate's practical demonstration. Training institutions and designated examiners should develop their own checklists for use in conducting the assessments in a complete and structured manner.

TABLE A-II/4 Guidelines for Assessment

Specification of minimum standard of competence

RATING FORMING PART OF A NAVIGATIONAL WATCH

Function: Navigation at the support level

STCW Competence	Knowledge, understanding	Performance Condition	Performance Behavior	Performance Standard
Steer the ship and comply with helm orders in the English language	Ise of magnetic and gyrocompasses Steady on a new course	At full sea speed, while on a northeasterly heading, when hearing the command in English, "Steer 342,*" *The assessor may select any course desired as long as it is more than 30° from the original heading. At least one assessment should include a turn to the right from the ordered course.	the candidate will turn the helm to bring the vessel to the new course and steady on the course of 342°.	 Repeat order. Turn the helm in the direction of the fewest degrees to the ordered course using no more than 15° of rudder. Reduce the rudder angle as the vessel approaches the course. Steady on the course of 342° with less than 5° of overshoot. State: she's steady on three four two.
Steer the ship and comply with helm orders in the English language	Use of magnetic and gyro-compasses Steer a course by gyro compass	In a sea state of 4 or less, when hearing the command in English, "Steer 342,"	the candidate will use the gyrocompass to steer the course of 342°.	 Repeat order. When steady on course state: steering three four two. Steer the course ordered within ± 3° (open ocean), and ±2° (near coastal) for 15 minutes.

STCW Competence	Knowledge, understanding and proficiency	Performance Condition	Performance Behavior	Performance Standard
Steer the ship and comply with helm orders in the English language	Use of magnetic and gyro- compasses Steer a course by magnetic compass	In a sea state of 4 or less, when hearing the command in English, "Steer 342,"	the candidate will use the magnetic compass to steer the course of 342°.	 Repeat order. When steady on course state: steering three four two. Steer the course ordered within ± 5° (open ocean), and ± 3° (near coastal) for 15 minutes.
Steer the ship and comply with helm orders in the English language	Helm order Right (Starboard) 10	When hearing the command in English, "Right (Starboard) 10,"	the candidate will turn the helm until the rudder is right (starboard) 10°.	 Repeat order Immediately turn helm to right (starboard). Stop turning the helm when the rudder angle indicator reads right (starboard) 10°. State: the rudder is right (starboard) 10, or she's right (starboard) 10°.
Steer the ship and comply with helm orders in the English language	Helm order Left (Port) 20	When hearing the command in English, "Left (Port) 20,"	the candidate will turn the helm left (port) until the rudder angle indicator shows the rudder is at left (port) 20°.	 Repeat order. Immediately turn helm to left (port). Stop turning the helm when the rudder angle indicator reads left (port) 20°. State: the rudder is left (port) 20, or she's left (port) 20°.

STCW Competence	Knowledge, understanding and proficiency	Performance Condition	Performance Behavior	Performance Standard
Steer the ship and comply	Helm order	When hearing the	the candidate will turn the	5. Repeat order.
with neith orders in the English language	06 (1001)	command in English, "Left (Port) 20,"	rudder angle indicator shows	6. Immediately turn helm to left (port).
			une rudder 1s at 1eit (port) 20°.	7. Stop turning the helm when the
				rudder angle indicator reads left (port) 20°.
				8. State: the rudder is left (port) 20, or she's left (port) 20°.
Steer the ship and comply	Helm order	When hearing the	the candidate will turn the	1. Repeat order.
with helm orders in the English language	Hard right	command in English, "Hard Right" (Starboard),	helm to the right (starboard) until the rudder is at maximum right (starboard)	2. Immediately turn helm to right (starboard).
				3. Stop turning the helm when the
				rudder angle indicator reads the
				maximum right (starboard) rudder.
				4. The rudder is not jammed against the stops.
				5. State: the rudder is hard right (starboard), or she's hard right
				(starboard).

STCW Competence	Knowledge, understanding and proficiency	Performance Condition	Performance Behavior	Performance Standard
Steer the ship and comply with helm orders in the English language	Helm order Ease to 5	When the rudder is more than 5° right (starboard) or left (port), when hearing the command in	the candidate will turn the helm to reduce the angle of the rudder until the indicator shows the rudder angle is	 Repeat order. Immediately turn helm to reduce the rudder angle.
		English, "Ease to 5,	right (starboard) or left (port) 5°.	3. Stop turning the helm when the rudder angle indicator shows the rudder angle is right (starboard) or left (port) 5°.
				4. State: the rudder is right (starboard) or left (port) 5°.
Steer the ship and comply with helm orders in the English language	Helm order Midships; or, midships the wheel	When hearing the command in English, "Midships,"	the candidate will turn the helm to reduce the angle of the rudder until the rudder angle indicator shows the rudder angle is zero.	 Repeat order. Immediately turn helm to reduce the rudder angle.
	musmps the wheel		rudder angle is zero.	3. Stop turning the helm when the rudder angle indicator shows the rudder angle is zero.
				4. State: the rudder is midships.

STCW Competence	Knowledge, understanding and proficiency	Performance Condition	Performance Behavior	Performance Standard
Steer the ship and comply with helm orders in the English language	Helm order Shift your rudder	With the rudder at 15° right (starboard) rudder, when hearing the command in English, "Shift your Rudder,"	the candidate will turn the helm to the left (port) until the indicator shows the rudder angle is left (port) 15°.	 Repeat order. Immediately turn helm to the left (port). Stop turning the helm when the rudder angle indicator shows the rudder angle is left (port) 15°. State: the rudder is left (port) 15°.
Steer the ship and comply with helm orders in the English language	Meet her; or, check her	During a turn, when hearing the command in English, "Meet Her," or "Check Her,"	the candidate will turn the helm to reduce the angle of the rudder and apply counter rudder until the vessel stops turning.	 Repeat order. Immediately turn helm to reduce the rudder angle. Apply counter rudder until the vessel stops turning. Ease the wheel to midships. State: the vessel's heading is

STCW Competence	Knowledge, understanding and proficiency	Performance Condition	Performance Behavior	Performance Standard
Steer the ship and comply with helm orders in the English language	Helm order Steady as she goes	When hearing the command in English, "Steady as She Goes,"	the candidate will note the heading of the vessel, stop any swing of the ship, and steer in the direction noted when the command was given.	 Repeat order. Note the heading when the command was given. Immediately apply rudder to stop any
				swing of the ship.4. Steer in the direction noted.5. State: she's steady as she goes.
Steer the ship and comply with helm orders in the English language	Helm order Steer on the range	When hearing the command in English, "Steer on the range,"	the candidate will keep the vessel's heading the same as the direction of the range.	 Repeat order. Use the upper and lower range to keep the vessel's heading within 1° of the charted direction of the range for 5 minutes when the upper and lower ranges are aligned one over the other.
Steer the ship and comply with helm orders in the English language	Helm order Nothing to the right (Starboard)* *Nothing to the left (port) may also be used	When hearing the command in English, "Nothing to the right (Starboard),"	The candidate will keep the vessel from swinging to the right (starboard) and the vessel's heading from increasing.	 The vessel does not swing to the right (starboard). The vessel's heading does not increase for 5 minutes.

Performance Condition
At sea speed, when hearing the command to put the steering into hand
steering,
At sea speed, when hearing the command to put the steering into auto
pilot,
٠

within 2 of lookout, ship simulator, given a spproximate bearing of a condition in daylight of sound signal, light or other unlimited visibility object in degrees or points. through a field of view from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight,	Responsibilities of lookout, ship simulator, given a report all three objects. Including reporting the ship simulator, given a approximate bearing of a condition in daylight of sound signal, light or other unlimited visibility through a field of view from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight,	Responsibilities of lookout, On a ship or full mission the candidate will detect and including reporting the ship simulator, given a approximate bearing of a condition in daylight of sound signal, light or other unlimited visibility through a field of view from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight,	Responsibilities of lookout, ship simulator, given a approximate bearing of a condition in daylight of sound signal, light or other unlimited visibility through a field of view from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight,	cout, On a ship or full mission the candidate will detect and ship simulator, given a condition in daylight of there objects. a condition in daylight of the unlimited visibility through a field of view from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight,
s. through a field of view from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight, 4.	s. through a field of view from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight, 4.	s. through a field of view from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight,	s. through a field of view from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight,	through a field of view from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight, 4.
from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight, 4.	from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight, 4.	from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight, 4.	from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight, 4.	from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight, 4.
or 3.	or 3.	3. 3. 4.	3. 3. 4.	3. 3. 4.
ю. 4.	ر ب	£ 4	κ. 4.	£ 4.
		χ. 4.	κ. 4.	<u>κ</u> . 4.
degrees or points within ± 1 point or \pm 11.25°.	degrees or points within ± 1 point or \pm 11.25°.	degrees or points within ±1 point or ± 11.25°.	degrees or points within ± 1 point or \pm 11.25°.	degrees or points within ±1 point or ± 11.25°.

STCW Competence	Knowledge, understanding and proficiency	Performance Condition	Performance Behavior	Performance Standard
Keep a proper look out by sight and hearing	Responsibilities of lookout, including reporting the approximate bearing of a sound signal, light or other object in degrees or points	On a ship or full mission ship simulator, given a condition at night of unlimited visibility through a field of view from right ahead to 22.5 degrees abaft the beam on each side of the vessel and a sea state of four or less, and a large and small vessel and a buoy in sight,	the candidate will detect and report all three objects.	 Reports the lights the large vessel before it is within ten miles of own ship. Reports the lights of the small vessel before it is within 2 miles of own ship. Reports the light of the buoy before it is within 2 miles of own ship. Report the direction to all objects in degrees or points within ±1 point or ±
Keep a proper look out by sight and hearing	Responsibilities of lookout, including reporting the approximate bearing of a sound signal, light or other object in degrees or points	On a ship or full mission ship simulator, in any condition of visibility, when a sound is generated by any sound appliance listed in the International Navigation Rules,	the candidate will detect and report the direction of the sound.	 Report the direction of the sound in degrees or points within ±1 point or ± 11.25°.

STCW Competence	Knowledge, understanding and proficiency	Performance Condition	Performance Behavior	Performance Standard
Contribute to monitoring and controlling a safe	Procedures for the relief, maintenance and hand over of a watch	On a ship at sea, given traffic that has been reported to the officer of	the candidate will hand over the watch in accordance with the ordinary practice of good	 Tell the relief of: a. all objects sighted
		the watch, when the lookout relieve the watch,	seamanship.	b. objects sighted and not yet reported;
				c. past and present weather;
				d. any special instructions to be followed during the watch; and,
				e. the status of the running lights.
				2. The candidate allowed the lookout relief to acquire his or her night vision.
				3. Report "the lookout is relieved."

STCW Competence	Knowledge, understanding and proficiency	Performance Condition	Performance Behavior	Performance Standard
Contribute to monitoring	Procedures for the relief,	On a ship at sea, when	the candidate will hand over	1. Tell the relief:
and controlling a safe	maintenance and hand over	being relieved at the	the helm in accordance with	a. both the gyro and
watch	of a helm watch	helm,	the ordinary practice of good	magnetic course
			seamanship.	or helm position;
				b. the steering
				mode;
				c. the steering unit
				in use; and,
				d. the amount and
				direction of
				rudder needed to
				hold course.
				2. The candidate does
				turn over the helm
				while executing a
				helm order (the
				candidate waits until
				the order is
				completed).
				3. The helmsman
				states, "the wheel (or
				helm) is relieved."

STCW Competence	Knowledge, understanding and proficiency	Performance Condition	Performance Behavior	Performance Standard
Contribute to monitoring and controlling a safe watch	Use of appropriate internal communications and alarm systems	On a ship at sea,	the candidate will notify the officer of the watch when hearing the following alarms: 1. The ARPA guard ring intrusion alarm; 2. The gyro-compass failure alarm; 3. Smoke and/or heat detector alarms; 4. Running Light panel alarms; 5. The steering motor failure alarm; and, 6. The steering pump failure alarm.	 Immediately report each alarm to the Officer in Charge of the Watch. In the case of steering failures, immediately after notifying the Officer in Charge of the Watch: if not in hand steering, switch the steering to hand; midship the wheel; switch the motor or pump; test the steering response; and, when ordered by the watch officer, switch the steering to autopilot.